

PATENT ABSTRACTS OF JAPAN

(11)Publication number : **06-051831**

(43)Date of publication of application : **25.02.1994**

(51)Int.Cl.

G05D 3/00

G01B 7/34

G12B 5/00

(21)Application number : **04-307552** (71)Applicant : **SONY TEKTRONIX CORP**

(22)Date of filing : **21.10.1992** (72)Inventor : **KEI UEN SHII YANGU**

(30)Priority


Priority number : **91 779653** Priority date : **21.10.1991** Priority country : **US**

(54) TWO-DIMENSIONAL POSITION ADJUSTING DEVICE

(57)Abstract:

PURPOSE: To provide the two-dimensional position adjusting device which can two-dimensionally move a sample to be tested over a wide range while compensating temperature drift.

CONSTITUTION: The sample to be tested is held on a surface by a sample holder 17'. A movable supporter 21 is provided with a pair of PZT coaxial tubes 24 and 26 fixed on a base, and one inside coaxial tube of a pair of these PZT coaxial tubes is provided with a magnetic means 32 for magnetically supporting the sample holder. A control signal to be supplied to a pair of PZT coaxial tubes in this movable supporter 21 is adjusted, and the position of the sample holder is two-dimensionally adjusted. Thus, the position of the sample to be tested at an SMT (scanning tunnel microscope) can be adjusted with high accuracy over the wide range on a two-



dimensional X-Y plane to a probe chip.

LEGAL STATUS

[Date of request for examination] 24.06.1993

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration] dismissal

[Date of final disposal for application] 10.06.1997

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]